

[54] : HOLDING STRUCTURE FOR DISPLAYING APPARATUS

[75] Inventors: **Shuichi Chihara**, Tokyo; **Ryuta Kanno**; **Akitoshi Okuma**, both of Kanagawa, all of Japan

[73] Assignee: **Sony Corporation, Tokyo, Japan**

[21] Appl. No.: 385,464

[22] Filed: Jul. 27, 1989

[30] Foreign Application Priority Data

Aug. 8, 1988	[JP]	Japan	63-197720
Dec. 19, 1988	[JP]	Japan	63-319885

[51] **Int. Cl.⁵** **F16M 13/00**

[52] U.S. Cl. 248/284; 16/361;
16/366; 16/371; 248/291; 248/917

[58] **Field of Search** 248/917, 918, 284, 291;
16/357, 360, 361, 366, 371

[56] References Cited

U.S. PATENT DOCUMENTS

1,920,898	8/1933	Soule	16/360
2,208,887	7/1940	Westwood	16/360
2,335,581	11/1943	Cocanour	16/366 X
2,721,635	10/1955	Fuillerton	16/357 X
3,388,417	6/1968	Uppchurch	16/360 X

FOREIGN PATENT DOCUMENTS

58495	3/1923	Sweden	16/366
175	2/1909	United Kingdom	16/371
2144569	7/1984	United Kingdom .	

2200783 1/1988 United Kingdom .

Primary Examiner—David L. Talbott
Attorney, Agent, or Firm—Lewis H. Eslinger; Jay H. Maioli

[57] **ABSTRACT**

A holding structure for a displaying apparatus for a so-called wrap top type electronic apparatus includes a first holding portion and a second holding portion on each lateral side of the displaying apparatus. The first holding portion is turnably connected to one end of a holding member having its other end turnably carried by the main body of an electronic apparatus, whilst the second holding portion is slidably held by a slide guide member provided on the main body of the electronic apparatus for extending in its for and aft direction. A frictional unit is provided at least at one of the swinging portions between the first holding portion and a holding member, between a second holding portion and a slide guide member and between the holding member and the main body of the electronic apparatus for turnably holding the displaying apparatus with respect to the main body of the apparatus while enabling the pivot point of turning of the displaying apparatus with respect to the main body of the electronic apparatus to be moved back and forth with the opening and closure of the displaying apparatus and reducing the amount of shift of the center of gravity of the displaying apparatus to enlarge the size of the displaying apparatus.

11 Claims, 10 Drawing Sheets

